



**GREENchoice™**  
ADHESIVES

Better for you.  
Better for the environment.  
Better for building.  
**BETTER. PERIOD.**

## NAHB Specification Sheet for Residential Construction

November 24, 2009

To Whom It May Concern:

This letter has been sent to verify the compliance of Titebond® GREENchoice Projects & Repair Construction Adhesive with the new green building standard created by the National Association of Homebuilders (NAHB) and the International Code Council (ICC). This new consensus standard on green building is called the National Green Building Standard™ or ANSI ICC-700-2008.

According to the standard, Titebond® GREENchoice Projects & Repair Construction Adhesive can be used to meet Section 901.9.2. To qualify, an adhesive must meet very low established VOC limits as well as meet the criteria specified in GreenSeal's GS-36. Our product has a VOC of only 6.6 g/L and does meet the GS-36 criteria. This statement is based upon the current formulation of the product and the regulations in place at the time of this letter.

By using Titebond® GREENchoice Projects & Repair Construction Adhesive on your current green building project, you could be contributing up to five points under Section 901.9.2 of the National Green Building Standard.™

Please use this letter for specification purposes or call 1-888-533-9043 with further questions.

For a copy of the MSDS or TDS, please visit [www.TitebondGreenChoice.com](http://www.TitebondGreenChoice.com).